

This side toward engine.



GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS

GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS

GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS



Always Replace with the Best...
GENUINE FORD PARTS



TRACTOR AND IMPLEMENT DIVISION
FORD MOTOR COMPANY



GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS

GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS

GENUINE TRACTOR AND
Ford
REG. U.S. PAT. OFF.
IMPLEMENT PARTS



Always Replace with the Best...
GENUINE FORD PARTS



TRACTOR AND IMPLEMENT DIVISION
FORD MOTOR COMPANY

For Non-Commercial Use by Ntractorclub.com Members Only

www.ntractorclub.com

This side toward engine.



Always Replace with the Best...

GENUINE FORD PARTS



**TRACTOR AND IMPLEMENT DIVISION
FORD MOTOR COMPANY**



Always Replace with the Best...

GENUINE FORD PARTS



**TRACTOR AND IMPLEMENT DIVISION
FORD MOTOR COMPANY**

For Non-Commercial Use by Ntractorclub.com Members Only

This side toward engine.

Always Replace

with the Best...

INSTALLATION INSTRUCTIONS

Remove and replace by hand. To install, first apply film of oil to gasket and then hand turn until filter firmly meets base - - then twist one half turn (180°).

CAUTION: Do not over-tighten. Add one pint of oil to Engine to replace oil removed with filter.

ENGINE OIL



FILTER

This hydraulic oil filter has been made to Ford Tractor and Implement Division Specifications for Full Flow of Oil, dirt removal, and pressure requirements.

Replace original filter after 50 hours. Thereafter, replace every 200 hours, or more frequently if operating conditions are extremely dry.

Replace only with Engine Oil Filter



**C5NN-6714-B
ENGINE OIL FILTER**

Always Replace

with the Best...

INSTALLATION INSTRUCTIONS

Remove and replace by hand. To install, first apply film of oil to gasket and then hand turn until filter firmly meets base - - then twist one half turn (180°).

CAUTION: Do not over-tighten. Add one pint of oil to Engine to replace oil removed with filter.

ENGINE OIL



FILTER

This hydraulic oil filter has been made to Ford Tractor and Implement Division Specifications for Full Flow of Oil, dirt removal, and pressure requirements.

Replace original filter after 50 hours. Thereafter, replace every 200 hours, or more frequently if operating conditions are extremely dry.

Replace only with Engine Oil Filter



**C5NN-6714-B
ENGINE OIL FILTER**

For Non-Commercial Use by Ntractorclub.com Members Only